Get the best, in every aspect

MCC Cold full serve displays 2 levels



Fri-Jado's MCC Food Displays offer you the best, in every aspect



Up to 75%* more product visibility thanks to clever design. Because seeing is buying.



Highest capacity in a small footprint: Up to 30% more display area saves valuable floor space.



Maximum food quality and safety, longer shelf life and less waste thanks to superior hot & cold holding technologies. Which at the same time save up to 50% on energy consumption and costs.



Combine hot & cold displays side by side or back-to-back and choose from a variety of other options: Self-serve, self-serve with glass doors or full serve, drop-in or floor models, 2, 3 or 4 levels, a solid back or sliding glass doors for rear loading and holding technologies specially developed for packaged and unpackaged food.



Made from 99% recyclable components in a solar-powered factory, and equipped with energy saving hot & cold holding technologies, the MCC range reduces environmental impact and lowers your energy bill.

* Compared to the competition according to global ISO standards - TDA ISO 23953



Two presentation levels



OmniCold technology

MCC Cold full serve display

Features

- 2-level refrigerated full serve display cabinet
- Designed for unpackaged products
- 900, 1200 or 1500 mm wide
- Mirror glass sliding doors on the operator side
- Available with underframe or as a drop-in version that can be integrated in any store concept
- · Underframe available in any RAL colour
- Slim transparent shelves with adjustable height and angle
- LED lighting with natural colour reproduction on each shelf
- OmniCold technology extends shelf life of unpackaged food. An indirect and gentle cold airflow around the products, which is evenly distributed throughout the unit, generates a constant temperature while minimizing dehydration.
- Eco-friendly: R290 refrigerant | 3M0 Classification
- Product temperature maintained between -1°C and 4°C (3M0)
- Thermopane glass increased insulation
- Ready to plug in for quick and easy installation with the optional evaporation tray
- Total presentation area:
 - MCC 90-2: 0.85 m²
 - MCC 120-2: 1.17 m²
 - MCC 150-2: 1.49 m²

Accessories

- Bumper (underframe models)
- Evaporation tray
- Castor set (underframe models)
 Fixing system for price rails



Maximum food visibility




Models on underframe or drop-in version




	MCC 90-2 Cold full serve	MCC 120-2 Cold full serve	MCC 150-2 Cold full serve
Width	900 mm	1200 mm	1500 mm
Depth	750 mm	750 mm	750 mm
Height on stand	1420 mm	1420 mm	1420 mm
Height drop-in above worktop	520 mm	520 mm	520 mm
Weight net / gross	170 / 202 kg	200 / 238 kg	230 / 274 kg
Energy class EU Energy Efficiency Index (EEI)	C A G	D A	□ A ↑ G
Temperature class	3M0	3M0	3M0
Voltage	1N~ 230V	1N~ 230V	1N~ 230V
Frequency	50 Hz	50 Hz	50 Hz
Power	0.39 kW	0.48 kW	0.69 kW
Max. nominal current*	3.7 A	3 A	4.6 A
Electrical connection**	2-pole earthed plug 16A	2-pole earthed plug 16A	2-pole earthed plug 16A
Refrigerant/GWP	R290 / 3	R290 / 3	R290 / 3


^{*} Excl. optional evaporation tray (additional 0.57 kW / 2.5 A)


MCC Cold full serve on underframe





MCC Cold full serve drop-in







^{**} Length power cord appr. 1.5 m