



SCE CABINET BLAST CHILLER & FREEZERS

Made by Foster Refrigeration

Specification

- 304 s/s finish inside & out*
- 7 mm radiused interior walls with flush entry base and drain outlet
- No visible screws or dirt traps
- Fully removable fungicidal magnetic door gasket
- Fully removable static stainless steel wire racking from 6 to 17 shelves positions at 60 mm intervals (75mm in option)
- High density (43kgs/M3) CFC/HCFC-free 60 mm polyurethane foam insulation throughout
- Easy-to-clean built-in door profile handle design
- Spring loaded hinges for automatic door closing with 90° dwell
- 4 lockable castors supplied as standard
- Improved 690 mm depth allows alignment with standard kitchen furniture

*except rear clad and exterior base: galvanized steel

Microprocessor controls

- Easy to use, eSafe microprocessor controls - automatic detection of selected mode (food probe or time-controlled chill cycle)
- Hard chill, soft chill and freeze and defrost options
- Rotating LED hourglass effect: chilling in progress - Bar graph: cycle progress
- « Info » button displays current core temperature (probe-controlled cycle) or time remaining (time-controlled cycle)
- Clear, easy-to-read touch sensitive display screen with smooth wipe-clean surface

Extras

- HACCP: USB data transfer
- Electric vaporizer tray
- eDry: avoids mould and odour build-up
- Removable condensor filter
- Optional 75mm self-intervals



205 Carnalbanagh Road, Broughshane, Ballymena, Co. Antrim, BT42 4NY



EP 06-20



EP 12-35

Specs

	EP 06-12	EP 06-20	EP12-35	EP12-45	EP 17-60	EP 17-80
Dimensions (wxdxh)mm	755 x 690 x 870	755 x 690 x 870	755 x 690 x 1530	755 x 690 x 1530	755 x 690 x 1805	755 x 690 x 1805
Chill & Freeze capacity	12 Kg* 6 Kg**	20 Kg* 12 Kg**	35 Kg* 15 Kg**	45 Kg* 20 Kg**	60 Kg* 25 Kg**	80 Kg* 40 Kg**
Shelf position	6 GN 1/1 (325 x 530mm) + 600 x 400mm	6 GN 1/1 (325 x 530mm) + 600 x 400mm	12 GN 1/1 (325 x 530mm) + 600 x 400mm	12 GN 1/1 (325 x 530mm) + 600 x 400mm	17 GN 1/1 (325 x 530mm) + 600 x 400mm	17 GN 1/1 (325 x 530mm) + 600 x 400mm
Duty refrigeration	602 W	1410 W	2510 W	3235 W	4855 W	9820 W
Refrigerant	404 A	404 A	404 A	404 A	404 A	404 A
Voltage	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	400/3/50

* From +70°C to +10°C in 90' ** From +70°C to -18°C in 270'