



SILVERES



SERELIS

ISECO, to enjoy nice and healthy food.

Therefore, the preservation of food quality as well as the pleasure and safety of your customers will always remain at the heart of our concerns.

SERELIS, The user-friendly trolley for "A la Carte" service of meals in dining rooms or cafeterias. SERELIS trolleys ensure the preservation and serving of meals with perfect respect for temperature regulations and hygiene for hot and cold food storage.

- Capacity

Optimized capacity with the SERELIS line, 7 and 8 levels GN 1/1 and SERELIS Compact, 7 and 8 levels, GN 1/2.

- Integrated Refrigeration

Refrigeration of one or both cavities ensured by a state of the art compressor which is integrated and assembled on a rack to simplify maintenance.

- Easy to Use

Refrigeration cycles and temperatures can be either pre-programmed or manually programmed. It is possible to program the shelves level by level with 3 different temperature pre-settings. The small size of SERELIS and its 6 wheels allow for exceptional manoeuvrability.



• Thermocontact

The thermocontact, invented and improved over the years by ISECO, is the only existing system that smoothly resets temperatures while delivering quality results.

SERELIS allows simultaneous temperature resetting and maintenance for regular or special products, in several or individual portions, for a single cycle thanks to the possible pre-selection of three different temperatures inside the same cavity.

The stability of the heating shelves ensures that the temperature is maintained, even after the trolley is unplugged.

Retherm precision allows the use of all types of containers : aluminium or polypropylene disposables or porcelain or stainless steel plates in all shapes and sizes.

The new thermocontact shelves, developed for SERELIS, allow a new refrigeration cycle to be ensured in less than two hours after the end of retherming.

• Hygiene ①

All HACCP guidelines for hygiene and cleaning are met : in the heating cavity, the thermocontact shelves block has been designed to pivot out for complete accessibility of the retherming compartment.

The new thermocontact shelves with integrated resistances offer a smooth surface for easy cleaning.

In the cooling cavity, the sliding rack is completely removable for the same purpose.



SERELIS

SERELIS and SERELIS compact have a unique working design for use in wards and dining rooms.



• Energy saving ②

Operating SERELIS is very energy efficient ; each shelf is individually regulated by programmable thermostat.

• Tracking ③

The onboard control panel displays the temperature in the cavities in real time as well as the time left in the retherm cycle and any interruptions to the cycle. The HACCP program option records the temperature during all phases of the cycle. This data is then radioed to a PC for review and record.



SERELIS and SERELIS Compact are extremely versatile enabling the connection between production units and wards. Their reinforced chassis ensure a strong protection and can also be equipped with a mechanical traction system.



①



②



③

• Much easier to manoeuvre

Would you like to enhance the ergonomics of the SERELIS trolley? The "motorization" option provides a retractable variable-speed motorized drive wheel, which allows you to move the trolley with virtually no effort.

The battery-powered motor is controlled easily and safely using a throttle placed near the handle. Manoeuvring and parking are very easy even in narrow spaces, and ramps can be navigated effortlessly.



• A trolley you can customize

ISECO provides you with a wide choice of colours and finishes for Serelis, letting you tailor its appearance to match the decor in your environment. Your Serelis should look as good as it works!

For further information, please contact the distributor of your area.



Technical characteristics

		Nb of shelves	Dimensions (mm)	Power (kW)
SERELIS 7.2 Isolé		7	L 1460 / w 680 / h 1015	5,3
SERELIS 8.2 Isolé		8	L 1460 / w 680 / h 1015	6,1
SERELIS 7.2.1 Fresh		7	L 1460 / w 680 / h 1015	6,5
SERELIS 8.2.1 Fresh		8	L 1460 / w 680 / h 1015	7,2
SERELIS 7.2 Fresh		7	L 1460 / w 680 / h 1015	6,5
SERELIS 8.2 Fresh		8	L 1460 / w 680 / h 1015	7,2
SERELIS 7 Isolé		7	L 1050 / w 680 / h 1015	5,3
SERELIS 8 Isolé		8	L 1050 / w 680 / h 1015	6,1
SERELIS 7 Fresh		7	L 1050 / w 680 / h 1015	6,1
SERELIS 8 Fresh		8	L 1050 / w 680 / h 1015	6,8
SERELIS Compact 7.2 Isolé		7	L 1320 / w 680 / h 1015	3,6
SERELIS Compact 8.2 Isolé		8	L 1320 / w 680 / h 1015	4,1
SERELIS Compact 7.2.1 Fresh		7	L 1320 / w 680 / h 1015	4,3
SERELIS Compact 8.2.1 Fresh		8	L 1320 / w 680 / h 1015	4,8
SERELIS Compact 7.2 Fresh		7	L 1320 / w 680 / h 1015	4,3
SERELIS Compact 8.2 Fresh		8	L 1320 / w 680 / h 1015	4,8
SERELIS Compact 7 Isolé		7	L 910 / w 680 / h 1015	3,6
SERELIS Compact 8 Isolé		8	L 910 / w 680 / h 1015	4,1
SERELIS 14 Isolé		7	L 1710 / w 680 / h 1015	10,6
SERELIS 16 Isolé		8	L 1710 / w 680 / h 1015	12,1



ISECO International

Minervum 7137 • 4817 ZN BREDA The Netherlands
Tél. +31 76 572 36 11 • Fax +31 76 572 36 01
Internet site: www.iseco.eu • E-mail: info@iseco.eu

Produced in EU, ISECO SAS - SaintPhal, FRANCE